

WEEBILL LAB Camera Compatible List

Updated on October 26, 2018 (corresponding to the firmware version of stabilizer: V1.82, image transmission stabilization version V1.13)  
The camera models listed in the table can complete the balance adjustment on the WEEBILL LAB and achieve the stabilization effect when paired with compatible lenses.  
The camera functions that WEEBILL LAB can control will be shown in the "camera control function" column and will be improved and added with the list.

Brand	Camera Model	Compatible Camera Control Cable	Grip Control	APP Control	Support Image Transmission or not	Precautions for camera-lens settings	Camera Firmware Version	Firmware Update Plan	Compatible Lens
Sony	A9	Micro USB _____ Type C or _____ Micro USB Multi	1. Take photos recording video 2. Start/stop recording video 3. Manual follow focus (with follow focus motor) 4. Aperture adjustment 5. Shutter speed adjustment 6. ISO adjustment	1. Take photos 2. Start/stop recording video 3. Aperture adjustment 4. Shutter speed adjustment 5. ISO adjustment 6. White balance adjustment	Yes	1. Selected MENU > USB Connection > PC Remote 2. Set the remote computer control as computer + camera device;	V1.10	/	FE 16-35mm F2.8 GM FE 12-24mm F4 G Vario-Tessar T* FE 16-35 mm F4 ZA OSS FE 28-70 mm F3.5-5.6 OSS FE 28 mm F2.8 DAi Distagon T* FE 35 mm F1.4 ZA Sonnar T* FE 35 mm F2.8 ZA FE 50mm F1.8 Sonnar® T* FE 55mm F1.8 ZA FE 85 mm F1.4 GM E 18-135mm F3.5-6.3 OSS E 10-18 mm F4 OSS E 18-135mm F3.5-6.3 OSS E 10-18 mm F4 OSS E 18-135mm F3.5-6.3 OSS E 18-200 mm F3.5-6.3 OSS LE Sonnar® T* E 24 mm F1.8 ZA (90MA) 30mm F1.4
	A7M3								
	A7R3								
	A7R2								
	A7S2								
	A6500								
Panasonic	A6300						V1.10	/	
	A6000						V3.20	/	
	GH5s	Micro USB _____ Type C	1. Take photos 2. Start/stop recording video 3. Manual follow focus (with follow focus motor) 4. Aperture adjustment 5. Shutter speed adjustment 6. ISO adjustment	1. Take photos 2. Start/stop recording video 3. Aperture adjustment 4. Shutter speed adjustment 5. ISO adjustment 6. White balance adjustment	Yes	Set the camera USB mode to PC (USB)	V1.1	/	EICA DG Vario-Elmarit 6-18mm f2.8-4.0 ASPH Lumix G X Vario 12-35mm f2.8 II ASPH POWER OIS LEICA DG SUMMILUX 15mm f1.7 ASPH Lumix G 25mm f1.7 (H4025GK) LUMIX G MACRO 30mm f2.8 ASPH MEGA OIS
	GH5				Yes		V2.2		

Note: 1. This form will be updated in real time with the firmware which will be subject to change without a prior notice.  
2. Balance adjustment is shown in the attached table.  
3. Camera models that are not listed in the table will be adapted in the future according to market feedback.

Attached Table:

1. \*Can be balanced at any focal length\* means the balance adjustment can be achieved for both the ends of the zoom lens.  
2. The follow focus is installed with the lens pointing direction as the front. The left side and the right side of the lens can be installed with the follow focus (the installation mode is not fixed and you can try it by yourself).  
3. The camera models and lenses that are not listed in the table can be balanced by users. The cameras that can achieve balance adjustment and are within the bearing range can be mounted on the WEEBILL LAB.

A7M3	ario-Tessar T* E 16-70mm F4 ZA OSS	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	E PZ 18-105mm F4 G OSS	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	E 18-200mm F3.5-6.3 OSS LE	Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side
		With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides
		With follow focus motor(zoom)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length	
		Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	The follow focus motor can be mounted on both sides	
	FE 28mm F2	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover		
		With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover		
		Camera only	√		x	No need to remove eyepiece cover		
	FE 24-70mm F4 ZA OSS	Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	Sonnar T* FE 35mm F2.8 ZA	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
Sigma 30mm f1.4 DC DN	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Distagon T* FE 35 mm F1.4 ZA	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Sonnar® T* FE 55mm F1.8 ZA	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 85mm F1.4 GM	Camera only	√	√		Need to remove eyepiece cover	The follow focus motor should be mounted on the left side	The vertical direction of the tilt axis is slightly unbalanced, and the holder of the follow focus can be clamped to the rear of the camera backing base.	
	With follow focus motor(focus)	√	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
	With follow focus motor(zoom)	√	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
A7R3	E 10-18mm F4 OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	FE 12-24mm F4 G	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		With follow focus motor(focus)	×	×	×	Can be balanced at any focal length and need to remove eyepiece cover		
	FE 16-35mm F2.8 GM	With follow focus motor(focus)	×	×	×	Can be balanced at any focal length and need to remove eyepiece cover		
		With follow focus motor(zoom)	×	×	×	Can be balanced at any focal length and need to remove eyepiece cover		
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	ario-Tessar T* E 16-70mm F4 ZA OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	E PZ 18-105mm F4 G OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side
		With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides
	E 18-200mm F3.5-6.3 OSS LE	With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length	
		With follow focus motor(zoom)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor should be mounted on the left side
		Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length	
		With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	The follow focus motor can be mounted on both sides	
FE 24-70mm F4 ZA OSS	Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	×	×	×	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 24-70 mm F2.8 GM	Camera only	×		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover			
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover			
	Camera only	√		x	No need to remove eyepiece cover			
FE 28mm F2	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover			
	Camera only	√		x	No need to remove eyepiece cover			
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover			
Sigma 30mm f1.4 DC DN	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Distagon T* FE 35 mm F1.4 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Sonnar T* FE 35mm F2.8 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 50mm F1.8	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Sonnar® T* FE 55mm F1.8 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 85mm F1.4 GM	Camera only	√	√		Need to remove eyepiece cover	The follow focus motor should be mounted on the left side	The vertical direction of the tilt axis is slightly unbalanced, and the holder of the follow focus can be clamped to the rear of the camera backing base.	
	With follow focus motor(focus)	√	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
	With follow focus motor(zoom)	√	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
A7S2	E 10-18mm F4 OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
	FE 12-24mm F4 G	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
	FE 16-35mm F2.8 GM	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	ario-Tessar T* E 16-70mm F4 ZA OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	E PZ 18-105mm F4 G OSS	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side
		With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides
	E 18-200mm F3.5-6.3 OSS LE	With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length	
		With follow focus motor(zoom)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor should be mounted on the left side
		Camera only	√		x	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length	
		With follow focus motor(focus)	√	√	√	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	The follow focus motor can be mounted on both sides	
FE 24-70mm F4 ZA OSS	Camera only	√		x	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	×	×	×	Can be balanced at 24-50mm focal length			
FE 24-70 mm F2.8 GM	With follow focus motor(focus)	×	×	×	No need to remove eyepiece cover			
	With follow focus motor(zoom)	×	×	×	No need to remove eyepiece cover			
	Camera only	√		x	No need to remove eyepiece cover			
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover			
FE 28mm F2	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover			
	Camera only	√		x	No need to remove eyepiece cover			
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover			
Sigma 30mm f1.4 DC DN	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Distagon T* FE 35 mm F1.4 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Sonnar T* FE 35mm F2.8 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 50mm F1.8	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Sonnar® T* FE 55mm F1.8 ZA	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
FE 85mm F1.4 GM	Camera only	√	√		No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
Panasonic GH5	LEICA DG Vario-Elmar 8-18mm f2.8-4.0 ASPH	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	Lumix G X Vario 12-35mm f2.8 II ASPH POWER OIS	Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(focus)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		With follow focus motor(zoom)	√	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Camera only	√		x	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	LEICA DG SUMMILUX 15mm f1.7 ASPH	Camera only	√		x	The follow focus motor should be mounted on the right side		
		With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover		
		With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover		
		Camera only	√		x	No need to remove eyepiece cover		
Lumix G 25mm f1.7 (H-H026GK)	Camera only	√		x	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(focus)	√	√	√	No need to remove eyepiece cover			
	With follow focus motor(zoom)	√	√	√	No need to remove eyepiece cover			